


Datasheet for: 113880



Spark erosion protected PU hose, Hose Ø 8x5, Roll of 25 m

Spark erosion protected PU hose, Temperature range -40 °C to 70 °C, Hose Ø 8x5, Working pressure 5 - 12 bar, Roll of 25 m . Blue polyurethane hose with an outer sheath made of black synthetic resin material. This sheath protects the inner PU tube from welding sparks. The sheath is not attached to the inner tube and can therefore be easily removed to enable conventional fittings to be installed. - Protects against welding sparks - Extremely flexible and non-kinking - Resistant to a large number of chemicals, oils, greases, acids, bases, heat, ageing, UV light

Type number	189.51
Article number	113880
EAN/barcode	 4047322031950
Your price	140,00 € / Role

Minimum order quantity

Price Unit	1
Quantity Unit	Role
Packaging Unit	1
Content	25 m
Minimum order quantity	1

Productdata

Colour	Black
Max. temperature range	70 °C
Max. working pressure	12 bar
Min. bending radius	19.0 mm
Min. temperature range	-40 °C
Min. working pressure	5 bar
Page No.	HK917
Reel length	25 m
Tube I.D.	5 mm
Tube O.D.	8.0 mm

Variants

<i>Article number</i>	<i>Tube I.D.</i>	<i>Tube O.D.</i>	<i>Price</i>
113880	5 mm	8.0 mm	140,00 € / Role
113879	4 mm	6.0 mm	121,25 € / Role
113881	8 mm	12.0 mm	247,75 € / Role