


Datasheet for: 106683



Valve disc HDM Connection 6 mm 3/2 monost. NC or NO

Valve disc for valve terminal HDM, Connection 6 mm, 3/2-way, NC, Monostable and 3/2-way, NO, monostable. These compact valve terminals, with a maximum flow rate of 800 NI/min, can be individually adapted to the specific conditions of each application thanks to the wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. Monostable (non-latching) version of manual control also available on request. The operating pressure is based on the installed input plates.

Type number	L 6
Article number	106683
EAN/barcode	 4047322286664
Your price	140,44 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Flow rate	500 NI/min
Function	3/2-way, NC, monostable and 3/2-way, NO, monostable
Manual control	latching
Max. temperature range	60 °C
Min. temperature range	-10 °C
Page No.	HK483
Piloting	Max. 16 (e.g. 16 spring return valves)
Power input	0.6 W per pilot
Protection IP	IP 65

Variants

Article number	Function	Price
106683	3/2-way, NC, monostable and 3/2-way, NO, monostable	140,44 € / Stk
106686	5/2-way, bistable (pulse valve)	136,68 € / Stk
106682	2 x 3/2-way, NO, monostable or 5/3-way, mid-position pressurised	140,44 € / Stk
106687	5/3-way, mid-position closed	140,44 € / Stk
106681	2 x 3/2-way, NC, monostable or 5/3-way, mid-position exhausted	140,44 € / Stk
106684	5/2-way, monostable	98,92 € / Stk
106685	5/2-way, monostable (uses only one pin, two signals assigned)	99,99 € / Stk