


Datasheet for: 102844


2/2-way solenoid valve, NC, force pilot operated, 24 V DC, Rp 1/2

2/2-way solenoid valve brass, NC, force pilot operated, 24 V DC, Rp 1/2, NBR, Medium temp. -20 °C to 85 °C, PN - 3 bar . Standard series, proven over many years, available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1217 G/0
Article number	102844
EAN/barcode	 4047322157094
Your price	218,65 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	80.0 mm
B	70.0 mm
DN	16.0
Electrical connection	ISO 4400; cable socket (Pg 11P)
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	50 °C
Max. medium temperature	85 °C
Max. operating pressure	3 bar
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Page No.	HK318
Protection IP	IP65 (with connector socket fitted)
Sealant	NBR
Standard thread	Rp thread acc. to ISO 7-1
Thread	Rp 1/2
Type	3
Valve seat	Brass

Variants

Article number	Thread	Max. medium temperature	DN	Sealant	Price
102844	Rp 1/2	85 °C	16.0	NBR	218,65 € / Stk
102843	Rp 3/8	85 °C	16.0	NBR	218,65 € / Stk
136140	Rp 3/8	120 °C	16.0	FKM	235,02 € / Stk
136143	Rp 3/4	120 °C	19.0	FKM	251,90 € / Stk
137598	Rp 1 1/2	120 °C	32.0	FKM	921,97 € / Stk
136141	Rp 1/2	120 °C	16.0	FKM	235,02 € / Stk
136146	Rp 1 1/4	85 °C	28.0	NBR	536,49 € / Stk
136147	Rp 1 1/2	85 °C	32.0	NBR	618,13 € / Stk
136145	Rp 1	120 °C	25.0	FKM	573,42 € / Stk
136144	Rp 1	85 °C	25.0	NBR	392,61 € / Stk
137597	Rp 1 1/4	120 °C	28.0	FKM	770,53 € / Stk
136142	Rp 3/4	85 °C	19.0	NBR	209,93 € / Stk

More Pictures

