


Datasheet for: 100591


Service unit 3-part »multifix«, Metal container, Size 1, G 1/4

Service unit 3-part »multifix«, Metal container, Viewing tube, Size 1, G 1/4, Input pressure max. 20 bar, Control range 0.5-10 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	FRL 11 M-SR
Article number	100591
EAN/barcode	 4047322131971
Your price	170,77 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	137.8 mm
B	192.5 mm
Bowl	Metal container with viewing tube
C	67.0 mm
Condensate drain	Semi-automatic
D	125.5 mm
DN	6.0
Filter rating	5.0 μm
Flow rate	1100 l/min
Flow rate measurement	At $P_1 = 8 \text{ bar}$, $P_2 = 6 \text{ bar}$ and pressure drop $\Delta_p = 1 \text{ bar}$
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	20 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK093
Pressure gauge display max.	16.0 bar
Pressure gauge display min.	0.0 bar

Sealant
 Series
 Sight dome
 Size
 Spring bonnet
 Thread

NBR
 multifix
 Zinc-glass-NBR
 1
 POM-brass
 G 1/4

Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	DN	Price
100591	G 1/4	Die-cast zinc	5.0 μm	1100 l/min	1	6.0	170,77 € / Stk
100592	G 3/8	Die-cast zinc	5.0 μm	1100 l/min	1	10.0	170,77 € / Stk
100593	G 1/2	Die-cast zinc	5.0 μm	3000 l/min	3	15.0	206,19 € / Stk
100594	G 3/4	Die-cast zinc	5.0 μm	3000 l/min	3	20.0	206,19 € / Stk
100595	G 1	Aluminium	40.0 μm	11300 l/min	5	25.0	512,89 € / Stk
133129	G 3/4	Die-cast aluminium	5.0 μm	9500 l/min	4	20.0	473,52 € / Stk
133130	G 1	Die-cast aluminium	5.0 μm	9500 l/min	4	25.0	473,52 € / Stk

More Pictures

