


Datasheet for: 113878



Anti-static hose (PU), black, Hose Ø 12x8, Roll of 25 m

Anti-static hose (PU), black, Temperature -40 °C to 70 °C, Hose Ø 12x8, PN at 26 °C/65 °C max. 6.21/3.1 bar, Roll of 25 m . Ether based polyurethane hose. The hose is conductive (insulating). We commend using antistatic tube fittings to connect it. Applications: Electrical systems, medical equipment, robotics, clean rooms in the semiconductor industry, packaging machines, powder coating machines.

Type number	189.04
Article number	113878
EAN/barcode	 4047322031936
Your price	219,75 € / Role

Minimum order quantity

Price Unit	1
Quantity Unit	Role
Packaging Unit	1
Content	25 m
Minimum order quantity	1

Productdata

Max. temperature range	70 °C
Min. bending radius	28.6 mm
Min. temperature range	-40 °C
Page No.	HK917
Reel length	25 m
Specific volume resistance	9.9x10 ⁹ Ohm-cm
Static discharge	Acc. to EIS Std. 541
Surface resistance	9.9x10 ⁹ Ohm-cm
Tube I.D.	8 mm
Tube O.D.	12.0 mm
Working pressure at 25 °C	6.21 bar
Working pressure at 65 °C	3.1 bar

Variants

<i>Article number</i>	<i>Tube I.D.</i>	<i>Tube O.D.</i>	<i>Working pressure at 25 °C</i>	<i>Working pressure at 65 °C</i>	<i>Price</i>
113878	8 mm	12.0 mm	6.21 bar	3.1 bar	219,75 € / Role
113875	2.4 mm	4.0 mm	7.24 bar	3.45 bar	33,00 € / Role
113876	4 mm	6.0 mm	6.21 bar	3.1 bar	59,25 € / Role
113877	5 mm	8.0 mm	6.89 bar	3.45 bar	99,25 € / Role