


Datasheet for: 101211


Stainless steel filter, 1.4404, 50 µm, G 1/4

Stainless steel filter, 1.4404, 50 µm, G 1/4, Input pressure max. 50 bar, Medium / ambient temperature max. 80 °C . Stainless steel filters containing no non-ferrous metals for use in the food processing, chemical, mining, plant construction and special machinery industries as well as in the medical technology.

Type number	572.14
Article number	101211
EAN/barcode	 4047322101950
Your price	315,99 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	64.0 mm
B	139.0 mm
C	125.0 mm
Condensate drain	Locking screw
Filter rating	50.0 µm
Flow rate	2500 l/min
Flow rate measurement	At P ₁ = 6 bar and pressure drop Δ _p ≤ 0.6 bar
Housing	Stainless steel 1.4404 (AISI 316L)
Max. ambient temperature	80 °C
Max. input pressure	50 bar
Max. medium temperature	80 °C
Page No.	HK152
Sealant	FKM
Thread	G 1/4

Variants

Article number	Thread	Flow rate	Price
101211	G 1/4	2500 l/min	315,99 € / Stk
101212	G 1/2	3400 l/min	443,00 € / Stk

More Pictures

