


Datasheet for: 125329


Active charcoal filter »variobloc« Protective cage, Size 2, G 1

Active charcoal filter »variobloc« with PC container and protective cage, 0.003 mg/m³, Size 2, G 1, Input pressure max. 16 bar . Activated carbon filters are used to absorb oil vapour from the compressed air. The incoming compressed air should be dry and free of impurities (upstream connection of a micro-filter is recommended).

Type number	VAK 26 S
Article number	125329
EAN/barcode	 4047322397643
Your price	172,82 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	124.0 mm
Air quality acc. to ISO 8573.1	Class 1 dirt, class 1 oil
B	193.0 mm
Bowl	Polycarbonate container with protective cage
C	26.0 mm
Flow rate	1300 l/min
Flow rate measurement	At P ₁ = 7 bar and pressure drop Δp = 0,1 bar
Max. ambient temperature	50 °C
Max. input pressure	16 bar
Max. medium temperature	50 °C
Page No.	WEB
Residual oil content	0.003 mg/m ³
Series	variobloc
Size	2
Thread	G 1

Variants

Article number	Thread	Flow rate	Size	Price
125329	G 1	1300 l/min	2	172,82 € / Stk
125325	G 1/4	800 l/min	1	92,89 € / Stk
125327	G 1/2	1200 l/min	2	133,79 € / Stk
125328	G 3/4	1300 l/min	2	133,79 € / Stk
125326	G 3/8	1000 l/min	1	92,89 € / Stk

More Pictures

