


Datasheet for: 100246


Service station SAFETY »FUTURA«, Size 2, G 1/2

Service station SAFETY »FUTURA«, Ball valve - start-up valve - pressure regulator, Size 2, G 1/2, Input pressure 2.5 - 16 bar . These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Type number	FU 1003
Article number	100246
EAN/barcode	 4047322246224
Your price	173,22 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	189.0 mm
B	150.0 mm
C	110.0 mm
Connecting thread	Material: Die-cast zinc
Diaphragms	NBR
Filter element	Cellpor (PE)
Filter rating	5.0 μm
Flow rate	4500 l/min
Flow rate measurement	At $P_1 = 10 \text{ bar}$, $P_2 = 6.3 \text{ bar}$ and pressure drop $\Delta p = 1 \text{ bar}$
Housing	PA66 GF60
Max. control range	8.0 bar
Max. input pressure	16 bar
Max. temperature range	50 °C
Medium	Compressed air, neutral gases
Min. control range	2.5 bar
Min. input pressure	2.5 bar
Min. temperature range	-10 °C
Page No.	HK051
Page No. SF	SF024

Pressure gauge display max.	10.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	FUTURA
Size	2
Thread	G 1/2
Vent port	Silencer (ball valve)

Variants

Article number	Thread	Flow rate	Size	Price
100246	G 1/2	4500 l/min	2	173,22 € / Stk
100244	G 3/8	1900 l/min	1	126,87 € / Stk
100243	G 1/4	1900 l/min	1	126,87 € / Stk
100245	G 3/8	4500 l/min	2	173,22 € / Stk
100247	G 3/4	10000 l/min	4	403,64 € / Stk
100248	G 1	10000 l/min	4	403,64 € / Stk

More Pictures

