


## Datasheet for: 116424


**Service unit 3-part »G«, PC container, 5 µm, Size 400, G 3/8**

Service unit 3-part »G«, PC container, Protective cage, 5 µm, Size 400, G 3/8, Input pressure max. 10 bar, Control range 1.5-9 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, centrifugal separator and proportional lubricator.

Type number	GFRL 32 A
Article number	116424
EAN/barcode	 4047322308458
Your price	174,47 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	236.0 mm
B	214.5 mm
Bowl	Polycarbonate container with protective cage
C	48.0 mm
Condensate drain	Fully-automatic
D	166.5 mm
Filter rating	5.0 µm
Flow rate	2950 l/min
Flow rate measurement	At P <sub>1</sub> = 8 bar, P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar
Housing	Die-cast aluminium
Max. ambient temperature	70 °C
Max. control range	9.0 bar
Max. input pressure	10 bar
Max. medium temperature	70 °C
Min. control range	1.5 bar
Page No.	WEB
Page No. AS	AS034
Sealant	NBR
Series	G
Sight dome	Brass/POM
Size	400

Spring bonnet  
 Thread

 POM  
 G 3/8

## Variants

Article number	Thread	Flow rate	Size	Condensate drain	Price
116424	G 3/8	2950 l/min	400	Fully-automatic	174,47 € / Stk
116426	G 1/2	2950 l/min	400	Fully-automatic	174,47 € / Stk
116422	G 1/2	1400 l/min	300	Fully-automatic	131,05 € / Stk
116420	G 3/8	1400 l/min	300	Fully-automatic	131,05 € / Stk
116425	G 1/2	2950 l/min	400	Semi-automatic	138,86 € / Stk
116418	G 1/4	1100 l/min	300	Fully-automatic	131,05 € / Stk
116417	G 1/4	1100 l/min	300	Semi-automatic	93,01 € / Stk
116419	G 3/8	1400 l/min	300	Semi-automatic	93,01 € / Stk
116421	G 1/2	1400 l/min	300	Semi-automatic	93,01 € / Stk
116423	G 3/8	2950 l/min	400	Semi-automatic	138,86 € / Stk

## More Pictures

