


## Datasheet for: 102907


**2/2-solenoid valve,NC,force pilot operat.,230-240V,G1,PN0-14bar**

2/2-way solenoid valve brass,NC,force pilot operated,230-240V,50-60Hz,27VA, Medium temp. -10°C to 90°C, NBR+PA, G 1, PN - 14bar . Economy series available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1414
Article number	102907
EAN/barcode	 4047322159876
Your price	141,88 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	67.0 mm
B	104.0 mm
DN	25.0
Electrical connection	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	80 °C
Max. medium temperature	90 °C
Max. operating pressure	14 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK321
Protection IP	IP 65 (with connector socket fitted)
Sealant	NBR
Thread	G 1
Type	8
Valve seat	Brass

## Variants

<i>Article number</i>	<i>Thread</i>	<i>Max. operating pressure</i>	<i>DN</i>	<i>Price</i>
102907	G 1	14 bar	25.0	141,88 € / Stk
102904	G 3/8	14 bar	11.0	80,49 € / Stk
102905	G 1/2	14 bar	16.0	80,49 € / Stk
102906	G 3/4	14 bar	16.0	80,49 € / Stk
102908	G 1	16 bar	25.0	119,63 € / Stk

## More Pictures

