

Datasheet for: 102912



2/2-sol. valve brass,NC,pilot oper.,24VDC, G1, - 6bar

2/2-way solenoid valve brass, NC, force pilot operated, 24V DC, 14W, Medium temp. -10°C to 90°C, NBR+PA, G 1, PN - 6bar . Economy series available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1414 G
-------------	-----------

Article number	102912
----------------	--------

EAN/barcode



4047322159883

Your price	141,88 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	67.0 mm
B	104.0 mm
DN	25.0
Electrical connection	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Function	normally closed (NC)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	80 °C
Max. medium temperature	90 °C
Max. operating pressure	6 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Page No.	HK321
Protection IP	IP 65 (with connector socket fitted)
Sealant	NBR
Thread	G 1
Type	8
Valve seat	Brass

Variants

Article number	Thread	Max. operating pressure	DN	Price
102912	G 1	6 bar	25.0	141,88 € / Stk
102909	G 3/8	14 bar	11.0	102,16 € / Stk
102910	G 1/2	14 bar	16.0	111,59 € / Stk
102911	G 3/4	14 bar	16.0	111,59 € / Stk

More Pictures

