


Datasheet for: 103175


Ball valve standard design, red steel lever, IT/IT, G 2 1/2

Ball valve standard design, red steel lever, IT/IT, nickel-plated brass, Operating temp. -15 °C to 90 °C, G 2 1/2, PN max. 40 bar . Applications: Compressed air, water, non-toxic and non-corrosive gases, heating systems, agriculture.

| | |
|----------------|--|
| Type number | 330.10-R |
| Article number | 103175 |
| EAN/barcode |  4047322396509 |
| Your price | 174,90 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|----------------------------|---|
| A | 248.0 mm |
| B | 97.0 mm |
| Ball | Chrome-plated brass |
| Ball seal | PTFE |
| DN | 65.0 |
| E | 18.5 mm |
| F | 18.5 mm |
| Hand lever | Steel, with plastic coating |
| L | 133.0 mm |
| Material | Nickel-plated brass |
| Max. operating temperature | 90 °C |
| Min. operating temperature | -15 °C |
| PN | 40 bar |
| Page No. | HK270 |
| Page No. TS | TS005 |
| Standard thread | G thread acc. to DIN EN ISO 228-1 |
| Stem seal | 2 O-rings HNBR/EPDM peroxide crosslinked, sealing ring PTFE |
| Thread | G 2 1/2 |
| Thread material | Brass with a bare metal surface |

Variants

| Article number | Thread | DN | Price |
|----------------|---------|------|----------------|
| 103175 | G 2 1/2 | 65.0 | 174,90 € / Stk |
| 103167 | G 1/4 | 8.0 | 11,76 € / Stk |
| 103172 | G 1 1/4 | 32.0 | 40,42 € / Stk |
| 103174 | G 2 | 50.0 | 90,51 € / Stk |
| 103171 | G 1 | 25.0 | 25,17 € / Stk |
| 103173 | G 1 1/2 | 40.0 | 59,41 € / Stk |
| 103170 | G 3/4 | 20.0 | 17,94 € / Stk |
| 103169 | G 1/2 | 15.0 | 13,16 € / Stk |
| 103168 | G 3/8 | 10.0 | 12,35 € / Stk |
| 103176 | G 3 | 80.0 | 247,32 € / Stk |

More Pictures

