


Datasheet for: 103529



Brass ball valve, Pneumat. actuation drive double-acting, Rp 2

2-way brass ball valve, Pneumat. actuation drive double-acting, Operating temperature max. 70 °C, Rp 2, DN 50, PN max. 25 bar . 2-way cock, full bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Type number	350.215
Article number	103529
EAN/barcode	 4047322075688
Your price	334,19 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	137.0 mm
Angle of rotation	90 °
B	191.0 mm
D	45.0 mm
DN	50.0
L	140.0 mm
Material actuator	Anodised aluminium
Material ball valve	Nickel-plated brass, with ISO flange plate
Max. operating temperature	70 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-20 °C
PN	25 bar
Page No.	HK299
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 2
Valve adapter	Supplied as standard
Version	double-acting
a/f	70 mm

Variants

Article number	Thread	DN	PN	a/f	Price
103529	Rp 2	50.0	25 bar	70 mm	334,19 € / Stk
103521	Rp 1/2	15.0	40 bar	26 mm	238,22 € / Stk
103522	Rp 1/2	15.0	40 bar	26 mm	162,62 € / Stk
103523	Rp 3/4	20.0	40 bar	32 mm	240,21 € / Stk
103524	Rp 3/4	20.0	40 bar	32 mm	171,95 € / Stk
103525	Rp 1	25.0	40 bar	41 mm	245,55 € / Stk
103526	Rp 1	25.0	40 bar	41 mm	217,47 € / Stk
103527	Rp 1 1/4	32.0	40 bar	50 mm	236,47 € / Stk
103528	Rp 1 1/2	40.0	25 bar	55 mm	255,12 € / Stk
103530	Rp 2 1/2	65.0	25 bar	83 mm	494,37 € / Stk
103531	Rp 3	80.0	16 bar	98 mm	600,61 € / Stk

More Pictures

