

Datasheet for: 103674


Intermediate flange blocking flap, Pneum. actuation drive, DN 40

Intermediate flange blocking flap, Pneumat. actuation drive, single-acting, Operating temp. -15°C to 120°C, DN 40, PN max. 16 bar . Butterfly valves with pneumatic actuator. Pneumatic actuators, double- or single acting version. For water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide. Not recommended for hydrocarbons, oils or greases.

Type number	350.5040B
-------------	-----------

Article number	103674
----------------	--------

EAN/barcode	
-------------	--



4047322338912

Your price	334,19 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Angle of rotation	90 °
B	38.0 mm
DN	40.0
Disc	Stainless steel CF8M/1.4404
H1	68.0 mm
H2	108.0 mm
H3	238.0 mm
Housing	Grey cast iron GG25 epoxy resin coated, RAL 5015 color
L	94.0 mm
Material actuator	Anodised aluminium
Max. operating pressure	16 bar
Max. operating temperature	120 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-15 °C
Min. pilot pressure	5.0 bar
Page No.	HK307
Sealant	EPDM
Sealant actuator	NBR

Selector shaft
 Selector shaft
 seal
 Valve adapter
 Version

SS416

EPDM

Supplied as standard, operated by a 3/2- or 5/2-way valve
 single-acting - spring to close

Variants

Article number	DN	Price
103674	40.0	334,19 € / Stk
103679	125.0	756,47 € / Stk
103678	100.0	625,42 € / Stk
103675	50.0	335,84 € / Stk
103676	65.0	383,37 € / Stk
103677	80.0	452,32 € / Stk
103680	150.0	950,89 € / Stk

More Pictures

