

## Datasheet for: 101579


**Active charcoal filter with differential pressure gauge, G 3/4**

Active charcoal filter with differential pressure gauge, 0.005 mg/m<sup>3</sup>, G 3/4, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C . For adsorbing vaporous media. A micro-filter must be connected upstream if dried air is not available.

Type number	431.3208
-------------	----------

Article number	101579
----------------	--------

EAN/barcode	 4047322087094
-------------	--

Your price	335,25 € / Stk
------------	----------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	83.0 mm
B1	414.0 mm
B2	315.0 mm
C	57.0 mm
D	403.0 mm
Filter element	Activated carbon
Flow rate	1000 l/min
Flow rate measurement	At P <sub>1</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.5%
Housing	Aluminium
Max. ambient temperature	60 °C
Max. indicating range of differential press. gauge	2.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. ambient temperature	5 °C
Min. indicating range of differential press. gauge	0.0 bar

Min. input pressure	4.0 bar
Min. medium temperature	5 °C
Page No.	HK139
Residual oil content	0.005 mg/m <sup>3</sup>
Thread	G 3/4
filter bowl	Aluminium

## Variants

Article number	Thread	Flow rate	Price
101579	G 3/4	1000 l/min	335,25 € / Stk
101576	G 1/4	500 l/min	297,17 € / Stk
101577	G 3/8	500 l/min	296,58 € / Stk
101578	G 1/2	500 l/min	296,11 € / Stk
101580	G 1	1500 l/min	462,34 € / Stk
101581	G 1 1/4	2650 l/min	517,44 € / Stk
101582	G 1 1/2	4150 l/min	568,00 € / Stk
101583	G 2	6650 l/min	707,89 € / Stk

## More Pictures

