


## Datasheet for: 102830



### 2/2-way solenoid valve, NO, directly operated, 230 V, 50 - 60 Hz

2/2-way solenoid valve brass, NO, directly operated, 230 V, 50 - 60 Hz, Medium temperature -15 °C to 100 °C, G 1/4, PN - 9 bar . Standard series, proven over many years, available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

|                |  |
|----------------|--|
| Type number    | MV 2235  |
| Article number | 102830   |
| EAN/barcode    | <br>4047322160421 |
| Your price     | 177,12 € / Stk   |

### Minimum order quantity

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

### Productdata

|                          |                                     |
|--------------------------|-------------------------------------|
| A                        | 80.0 mm                             |
| B                        | 40.0 mm                             |
| DN                       | 3.2                                 |
| Electrical connection    | ISO 4400; cable socket (Pg 11P)     |
| Function                 | normally open (NO)                  |
| Housing                  | Brass                               |
| Internal parts           | Stainless steel                     |
| Max. ambient temperature | 55 °C                               |
| Max. medium temperature  | 100 °C                              |
| Max. operating pressure  | 9 bar                               |
| Min. ambient temperature | -15 °C                              |
| Min. medium temperature  | -15 °C                              |
| Page No.                 | HK317                               |
| Protection IP            | IP65 (with connector socket fitted) |
| Sealant                  | FKM                                 |
| Standard                 | G thread acc. to DIN EN ISO 228-1   |
| thread                   | G 1/4                               |
| Thread                   | G 1/4                               |
| Type                     | 2                                   |
| Valve seat               | Brass                               |

## Variants

| Article number | Thread | Max. operating pressure | Max. medium temperature | DN  | Sealant | Type | Price          |
|----------------|--------|-------------------------|-------------------------|-----|---------|------|----------------|
| 102830         | G 1/4  | 9 bar                   | 100 °C                  | 3.2 | FKM     | 2    | 177,12 € / Stk |
| 102827         | Rp 1/8 | 20 bar                  | 80 °C                   | 2.4 | NBR     | 7    | 115,99 € / Stk |
| 102828         | Rp 1/8 | 20 bar                  | 100 °C                  | 2.4 | FKM     | 1    | 140,57 € / Stk |
| 102829         | G 1/4  | 9 bar                   | 80 °C                   | 3.2 | NBR     | 2    | 158,02 € / Stk |

## More Pictures

