


Datasheet for: 102756


Digital snap on display, 4-digit LCD display of -1999 to +9999

Digital snap on display for pressure transducer, 4-digit LCD display of -1999 to +9999, Operating temp. °C to +50 °C . The digital plug-in display is freely programmable and easily mounted, and can therefore be retrofitted in a very short time without any problems, even if the transmitter is already in use. No external power supply is required. Suitable for all 4 to 20 mA transmitters with a right-angle connector. Freely programmable by means of keys inside the display.

Type number	894.20
Article number	102756
EAN/barcode	 4047322122566
Your price	226,57 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Accuracy	± 0.2% ± 1 digit of span
Display	4-digit, 7-segment LCD display, digits 10 mm high
Electrical connection	Adapter for plug acc. to DIN EN 175301-803 A
Height	35.5 mm
Input signal	4 to 20 mA, 2-wire
Length	48.5 mm
Max. operating temperature	50 °C
Measuring range	-1999 to +9999 digits (min. and max. values freely scalable)
Page No.	HK236
Power supply	From 4 to 20 mA loop of transmitter
Protection IP	IP 65
Width	48.5 mm