


## Datasheet for: 124873


**Service unit 2-part »variobloc«, Protective cage, Size 2, G 1**

Service unit 2-part »variobloc«, PC container and protective cage, Size 2, G 1, Input pressure max. 16 bar, Temp. max. 50 °C. Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VW 26 S
Article number	124873
EAN/barcode	 4047322398626
Your price	226,83 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	194.0 mm
B	273.0 mm
Bowl	Polycarbonate container with protective cage
C	98.0 mm
Condensate drain	Manual
Diaphragms	NBR
Filter rating	40.0 µm
Flow rate	5000 l/min
Flow rate measurement	At P <sub>1</sub> = 10 bar, P <sub>2</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 1 bar
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	50 °C
Min. control range	0.5 bar
Page No.	WEB

Pressure gauge display max.	10.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	variobloc
Sight dome	PA
Size	2
Spring bonnet	POM
Thread	G 1

## Variants

Article number	Thread	Flow rate	Size	Price
124873	G 1	5000 l/min	2	226,83 € / Stk
124868	G 1/2	3400 l/min	2	192,35 € / Stk
124863	G 1/4	1500 l/min	1	130,67 € / Stk
124871	G 3/4	5000 l/min	2	192,35 € / Stk
124866	G 3/8	1800 l/min	1	130,67 € / Stk

## More Pictures

