

## Datasheet for: 103686


**Intermediate flange blocking flap, Manual lever, DN 125**

Intermediate flange blocking flap, Manual lever, Operating temperature -15 °C to 120 °C, DN 125, PN max. 16 bar . Butterfly valves with hand lever suitable for water/steam, seawater, salt water, ester, ketones, alkalis, caustic soda, sodium hydroxide. Not recommended for hydrocarbons, oils or greases.

Type number	350.6125B
Article number	103686
EAN/barcode	 4047322338899
Your price	227,62 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

B	59.0 mm
DN	125.0
Disc	Stainless steel CF8M/1.4404
H1	123.0 mm
H2	191.0 mm
H3	336.0 mm
Hand lever	GG25 epoxy resin coated
Housing	Grey cast iron GG25 epoxy resin coated, color RAL 5015
L	190.0 mm
Max. operating pressure	16 bar
Max. operating temperature	120 °C
Min. operating temperature	-15 °C
Page No.	HK308
Sealant	EPDM
Selector shaft	SS416
Selector shaft seal	EPDM
Shaft	SS416

## Variants

Article number	DN	Price
103686	125.0	227,62 € / Stk
103687	150.0	299,27 € / Stk
103685	100.0	169,14 € / Stk
103684	80.0	138,50 € / Stk
103683	65.0	120,80 € / Stk
103682	50.0	119,75 € / Stk
103681	40.0	113,70 € / Stk

## More Pictures

