


Datasheet for: 100716


Service unit 3-part »variobloc« with PC container, Size 2, G 1

Service unit 3-part »variobloc« with PC container, Size 2, G 1, Input pressure max. 16 bar, Medium / ambient temp. max. 50 °C . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VW 16
Article number	100716
EAN/barcode	 4047322212755
Your price	228,20 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	264.0 mm
B	274.0 mm
Bowl	Polycarbonate container
C	98.0 mm
Condensate drain	Manual
Diaphragms	NBR
Filter rating	40.0 µm
Flow rate	5000 l/min
Flow rate measurement	At P ₁ = 10 bar, P ₂ = 6 bar and pressure drop Δ _p = 1 bar
Housing	Die-cast zinc
Max. ambient temperature	50 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	50 °C
Min. control range	0.5 bar
Page No.	HK110

Pressure gauge display max.	10.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	variobloc
Sight dome	PA
Size	2
Spring bonnet	POM
Thread	G 1

Variants

Article number	Thread	Flow rate	Size	Price
100716	G 1	5000 l/min	2	228,20 € / Stk
100712	G 1/4	1500 l/min	1	124,00 € / Stk
100713	G 3/8	1800 l/min	1	124,00 € / Stk
100714	G 1/2	3400 l/min	2	191,83 € / Stk
100715	G 3/4	5000 l/min	2	191,83 € / Stk

More Pictures

