

Datasheet for: 103389


3-way ball valve, L-hole, nickel-plated brass, Rp 1 1/2, DN 40

3-way ball valve, L-hole, nickel-plated brass, Medium / ambient temp. -15 °C to 100 °C, Rp 1 1/2, DN 40, PN max. 16 bar . The medium can enter via any of the ports to allow several switching variants. 3-way ball valves for diverting media.

Type number	1083 G
Article number	103389
EAN/barcode	 4047322013185
Your price	179,15 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	195.0 mm
B	125.0 mm
Ball	Bright brass
Bore inball	35
DN	40.0
Hand lever	Aluminium, painted black
Housing	Nickel-plated brass
L	147.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Max. operating pressure at 20 °C	16 bar
Min. ambient temperature	-15 °C
Min. medium temperature	-15 °C
Page No.	HK295
Position indicator	Galvanised steel
Sealant	PTFE / FKM
Spring	Stainless steel
Standard thread	Rp thread acc. to ISO 7-1
Thread	Rp 1 1/2
Thread material	Bright brass

Variants

Article number	Thread	DN	Bore in ball	Max. operating pressure at 20 °C	Price
103389	Rp 1 1/2	40.0	35	16 bar	179,15 € / Stk
103383	Rp 1/4	8.0	10	40 bar	50,21 € / Stk
103384	Rp 3/8	10.0	13	40 bar	50,21 € / Stk
103385	Rp 1/2	15.0	13	40 bar	50,21 € / Stk
103386	Rp 3/4	20.0	18	40 bar	70,13 € / Stk
103387	Rp 1	25.0	23	25 bar	99,37 € / Stk
103388	Rp 1 1/4	32.0	29	16 bar	135,01 € / Stk
103390	Rp 2	50.0	44	16 bar	241,83 € / Stk

More Pictures

