

Datasheet for: 108391

Basic ejector »SBP-C«, Bleeder valve, Silencer, Nozzle size 2 mm

Basic ejector »SBP-C«, Bleeder valve, Silencer, Nozzle size 2 mm, Compressed air / vacuum connection 8/10 mm, NO . Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C. Properties:

- Vacuum generator with a single nozzle, available in six power ratings, with a high maximum vacuum value (85%)

- Connection of compressed air and vacuum with push-in coupling

- Basic housing with connection facility for a vacuum switch

- Maximum suction capacity with minimum compressed air consumption

- Minimum size, low weight

- Various power ratings for optimised air consumption

Applications:


- For universal use in handling systems with very high dynamic movements

- Handling all kinds of air-tight components

- For use in separation systems where space is restricted

- Construction of ejector blocks for centralised or decentralised individual control of suction pads



Type number	SBPC 20
Article number	108391
EAN/barcode	 4047322198912
Your price	229,61 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Body Plastic (impact-resistant)

Compressed air inlet	8 mm
Connection	Push-in coupling
Height	72.0 mm
Length	228.0 mm
Nozzle size	2.0 mm
Nozzle system	Brass
Page No.	WEB
Silencer	Plastic
Suction valve idle position	NO
Vacuum inlet	10 mm
Width	20.0 mm

Variants

Article number	Nozzle size	Compressed air inlet	Vacuum inlet	Price
108391	2.0 mm	8 mm	10 mm	229,61 € / Stk
108389	1.0 mm	6 mm	8 mm	191,35 € / Stk
108390	1.5 mm	6 mm	8 mm	200,15 € / Stk
108392	2.5 mm	8 mm	10 mm	242,26 € / Stk

More Pictures

