


Datasheet for: 103549



3-way brass ball valve, Pneumat. actuation drive, L-hole, Rp 1/2

3-way brass ball valve, Pneumat. actuation drive, L-hole, Operating temperature -20 °C to 70 °C, Rp 1/2, DN 15, PN max. 40 bar . 3-way cock, L-bore or T-bore, full bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback.

Type number	350.610/1
Article number	103549
EAN/barcode	 4047322076777
Your price	230,18 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	116.0 mm
Angle of rotation	90 °
B	133.0 mm
D	20.0 mm
DN	15.0
L	64.5 mm
Material actuator	Anodised aluminium
Material ball valve	Nickel-plated brass, with ISO flange plate
Max. operating temperature	70 °C
Max. pilot pressure	5.5 bar
Min. operating temperature	-20 °C
PN	40 bar
Page No.	HK300
Position	L 2
Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 1/2
Valve adapter	Supplied as standard
Version	double-acting
a/f	25 mm

Variants

Article number	Thread	DN	PN	a/f	Price
103549	Rp 1/2	15.0	40 bar	25 mm	230,18 € / Stk
103550	Rp 3/4	20.0	40 bar	31 mm	285,87 € / Stk
103551	Rp 1	25.0	40 bar	41 mm	346,90 € / Stk
103552	Rp 1 1/4	32.0	40 bar	55 mm	390,79 € / Stk
103553	Rp 1 1/2	40.0	25 bar	55 mm	517,10 € / Stk
103554	Rp 2	50.0	25 bar	67 mm	610,40 € / Stk

More Pictures

