

## Datasheet for: 141562


**Quick-connect coupling I.D. 19, Bright brass, G 1 ET**

Quick-connect coupling I.D. 19, Bright brass, G 1 ET, Operating pressure - 35 bar, Med. 7 ambient temp. -20 °C to 100 °C . Single-sided blocking and quick connect coupling with extremely high flow performance. To prevent injuries or a "whiplash" effect, we recommend that the plug-in nipple is held with one hand during uncoupling. These quick disconnect couplings are not suitable for direct attachment to pulsating tools. We recommend using our vibration dampers, according to ISO 6150 § 7.1. Areas of application: Machine and plant engineering, manufacturing industry, workshops.

Type number	419.15
Article number	141562
EAN/barcode	 4047322568340
Your price	179,90 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Connection	G 1 ET
DN	19
Flow rate	8700 l/min (air)
Flow rate measurement	at 6 bar and $\Delta_p = 0.5$ bar
Housing	Brass with a bare metal surface
Length	98.0 mm
Max. ambient temperature	100 °C
Max. medium temperature	100 °C
Min. ambient temperature	-20 °C
Min. medium temperature	-20 °C
Operating pressure	- 35 bar
Page No.	HK555
Page No. SK	SK037
Sealant	NBR
Sleeve	Brass with a bare metal surface
Spring	Stainless steel
Threaded piece	Brass with a bare metal surface

Valve  
 a/f

 Brass with a bare metal surface  
 41 mm

### Variants

Article number	Connection	Length	a/f	Price
141562	G 1 ET	98.0 mm	41 mm	179,90 € / Stk
141563	G 1 1/4 ET	98.0 mm	42 mm	215,88 € / Stk
141561	G 3/4 ET	95.0 mm	41 mm	179,90 € / Stk

### More Pictures

