


Datasheet for: 101160


Filter for high pressures up to 40 bar, 40 μm , G 3/8

 Filter for high pressures up to 40 bar, with manual bleeder valve, 40 μm , G 3/8, Medium temperature max. 60 °C . Centrifugal separators with a sintered filter element.

Type number	680.21
Article number	101160
EAN/barcode	 4047322112345
Your price	145,15 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	73.0 mm
B	194.0 mm
Bowl	Brass
C	32.5 mm
Condensate drain	Manual drain valve
Filter rating	40.0 μm
Flow rate	2650 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Aluminium
Max. ambient temperature	90 °C
Max. input pressure	40 bar
Max. medium temperature	60 °C
Page No.	HK143
Thread	G 3/8

Variants

Article number	Thread	Body	Flow rate	Price
101160	G 3/8	Brass	2650 l/min	145,15 € / Stk
101161	G 1/2	Brass	2650 l/min	143,50 € / Stk
101162	G 3/4	Brass	3350 l/min	165,87 € / Stk
101163	G 1	Brass	3350 l/min	166,58 € / Stk
101164	G 1 1/2	Aluminium	20000 l/min	736,55 € / Stk
101165	G 2	Aluminium	20000 l/min	736,55 € / Stk

More Pictures

