


Datasheet for: 100574


Service unit 2-part »multifix«, Protective cage, Size 3, G 3/4

Service unit 2-part »multifix«, PC container, Protective cage, Size 3, G 3/4, Input pressure max. 16 bar, Control range 0.5-10 bar . Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	CL 34 S
Article number	100574
EAN/barcode	 4047322125444
Your price	181,49 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	134.8 mm
B	246.3 mm
Bowl	Polycarbonate container with protective cage
C	99.0 mm
Condensate drain	Semi-automatic
D	147.3 mm
DN	20.0
Filter rating	5.0 μ m
Flow rate	3500 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK091
Pressure gauge display max.	16.0 bar

Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	multifix
Sight dome	PA
Size	3
Spring bonnet	POM-brass
Thread	G 3/4

Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	DN	Price
100574	G 3/4	Die-cast zinc	5.0 μm	3500 l/min	3	20.0	181,49 € / Stk
100571	G 1/4	Die-cast zinc	5.0 μm	1100 l/min	1	6.0	109,74 € / Stk
100572	G 3/8	Die-cast zinc	5.0 μm	1100 l/min	1	10.0	115,33 € / Stk
100573	G 1/2	Die-cast zinc	5.0 μm	3500 l/min	3	15.0	179,72 € / Stk
100575	G 1	Aluminium	40.0 μm	10500 l/min	5	25.0	499,74 € / Stk
133124	G 1	Die-cast aluminium	5.0 μm	9500 l/min	4	25.0	341,79 € / Stk
133123	G 3/4	Die-cast aluminium	5.0 μm	9500 l/min	4	20.0	341,79 € / Stk

More Pictures

