


Datasheet for: 100565



Mist oiler »multifix«, with metal container, Size 5, G 1

Mist oiler »multifix«, Metal container, Viewing tube, Size 5, G 1, Input pressure max. 20 bar, Medium / ambient temp. max. 60 °C . Proportional lubricators, oil can be filled under pressure.

Type number	L 55 M-SR
Article number	100565
EAN/barcode	 4047322155830
Your price	183,01 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	100.0 mm
B	322.9 mm
Bowl	Metal container with viewing tube
C	82.7 mm
D	240.2 mm
DN	25.0
Flow rate	18000 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Aluminium
Max. ambient temperature	60 °C
Max. input pressure	20 bar
Max. medium temperature	60 °C
Oil grade	CL 32 acc. to DIN 51517-ISO VG 32
Page No.	HK090
Sealant	NBR
Series	multifix
Sight dome	Zinc-glass-NBR
Size	5
Thread	G 1

Variants

Article number	Thread	Housing	Flow rate	Size	DN	Price
100565	G 1	Aluminium	18000 l/min	5	25.0	183,01 € / Stk
100561	G 1/4	Die-cast zinc	1900 l/min	1	6.0	67,67 € / Stk
100562	G 3/8	Die-cast zinc	1900 l/min	1	10.0	67,67 € / Stk
100563	G 1/2	Die-cast zinc	5000 l/min	3	15.0	86,43 € / Stk
100564	G 3/4	Die-cast zinc	5000 l/min	3	20.0	86,43 € / Stk
133122	G 1	Die-cast aluminium	18000 l/min	4	25.0	162,14 € / Stk
133121	G 3/4	Die-cast aluminium	18000 l/min	4	20.0	162,14 € / Stk

More Pictures

