

Datasheet for: 101645



Proportional control valve »posiflow«, 24 V DC, NC, G 1/4, DN 2.4

Proportional control valve »posiflow«, for water / oil, 24 V DC, NC, G 1/4, DN 2.4, Operating pressure difference max. 8 bar . For electronic flow control. For all applications where the flow rate of a liquid or gas has to be controlled. The valve features a special magnet armature and is characterised by low friction and a high dynamic response. If the valve is combined with a plug amplifier: The maximum / minimum current and frequency can be adjusted by means of integrated potentiometers. A current ramp can also be connected and adjusted with a potentiometer. This facilitates a slow change in the flow rate, even if the setpoint changes suddenly. If the setpoint is < 200 mV (< 0.4 / 4.4 mA), the piloting current is completely switched off, causing the valve to be de-energised (tightly closed function). We recommend combining these proportional valves with a plug amplifier. Benefits: - Compact and economical - Integrated temperature compensation - Precise control - Optimised flow with no water hammer - Ramp function assures a smooth response to step changes in the input signal - Disconnect function

FAN/harcode		
Article number	101645	
Type number	PV 2023	

Your price 184,24 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A B C DN Failsafe beha-	85.0 mm 40.0 mm 95.0 mm 2.4 Tight closure in case of loss of voltage
viour Housing Internal parts Max. ambient temperature Max. medium	Brass Stainless steel 75 °C
temperature	90 °C

Created on: 18. Juni 2020 User: 18. Juni 2020 Gast

Page: 1 / 2



Max. operating pressure difference Medium

Min. ambient temperature Min. medium temperature Page No.

Piloting Pressure range

Sealant Thread Valve disc Valve seat 8.0 bar

Air, neutral gases, water, oil

-10 °C

-10 °C

HK186


Via plug amplifier to 10 V, to 20 mA, 4 to 20 mA Vacuum to 8 bar


FKM G 1/4 FKM **Brass**

Variants

Article number	$ ho_{arrho}$		Max, Operating pressure difference	
A TOTAL STATE OF THE STATE OF T	Deau.	NO	Non	S. I.
101645	G 1/4	2.4	8.0 bar	184,24 € / Stk
101646	G 1/4	3.2	4.0 bar	184,24 € / Stk
101647	G 3/8	5.6	1.4 bar	200,98 € / Stk
101648	G 3/8	7.1	1.0 bar	200,98 € / Stk

More Pictures





RIEGLER & Co. KG Schützenstraße 27 72574 Bad Urach DE

Contact: +49 7125 9497-8320 +49 7125 9497-95 shop@riegler.de

Created on: 18. Juni 2020 User: Gast

Page: 2/2