


Datasheet for: 125347


**Service unit 2-part »variobloc«, Metal container, Size 2, G 1/2**

Service unit 2-part »variobloc«, Metal container incl. viewing tube and metal drip cap, Size 2, G 1/2, Input pressure max. 20 bar . Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VW 24 M
Article number	125347
EAN/barcode	 4047322170277
Your price	232,74 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	140.0 mm
B	273.0 mm
Bowl	Metal container with viewing tube
C	98.0 mm
Condensate drain	Manual
Diaphragms	NBR
Filter rating	40.0 $\mu\text{m}$
Flow rate	3400 l/min
Flow rate measurement	At $P_1 = 10 \text{ bar}$ , $P_2 = 6 \text{ bar}$ and pressure drop $\Delta_p = 1 \text{ bar}$
Housing	Die-cast zinc
Max. ambient temperature	80 °C
Max. control range	10.0 bar
Max. input pressure	20 bar
Max. medium temperature	50 °C
Min. control range	0.5 bar
Page No.	WEB

Pressure gauge display max.	10.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	variobloc
Sight dome	PA
Size	2
Spring bonnet	POM
Thread	G 1/2

## Variants

Article number	Thread	Flow rate	Size	Price
125347	G 1/2	3400 l/min	2	232,74 € / Stk
125345	G 1/4	1500 l/min	1	164,72 € / Stk
125346	G 3/8	1800 l/min	1	164,72 € / Stk
125348	G 3/4	5000 l/min	2	232,74 € / Stk
125349	G 1	5000 l/min	2	267,11 € / Stk

## More Pictures

