

Datasheet for: 106690



Valve disc HDM Connection 8mm 2x3/2 NO mono or 5/3 centre aerated

Valve disc for valve terminal HDM, Connection 8 mm, 3/2-way, NC, Monostable and 3/2-way, NO, monostable . These compact valve terminals, with a maximum flow rate of 800 Nl/min, can be individually adapted to the specific conditions of each application thanks tot he wide range of functions and various input and intermediate plates. Since each valve terminal is a customer-specific combination of a series of individual elements, the catalogue only lists the available input, intermediate and end plates as well as the different valve discs and the 25-pin multi-pole connectors. Suitable for filtered, unlubricated or lubricated compressed air. If lubrication is used, it must be continuous. Monostable (non-latching) version of manual control also available on request. The operating pressure is based on the installed input plates.

Type number	L 8
Article number	106690
EAN/barcode	4047322286732
Your price	146,20 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Flow rate
Function
Manual control
Max. temperature range
Min. temperature range
Page No.

800 Nl/min
3/2-way, NC, monostable and 3/2-way, NO, monostable latching
60 °C
-10 °C
HK484

Piloting Max. 16 (e.g. 16 spring return valves)

Power input 0.6 W per pilot

Protection IP IP 65

Created on: 18. Juni 2020

User: Gast

Page: 1 / 2



Variants

Aricle number	, S	
Ario). (3)
106690	3/2-way, NC, monostable and 3/2-way, NO, monostable	146,20 € / Stk
106693	5/2-way, bistable (pulse valve)	141,96 € / Stk
106688	2 x 3/2-way, NC, monostable or 5/3-way, mid-position exhausted	146,20 € / Stk
106689	2 x 3/2-way, NO, monostable or 5/3-way, mid-position pressurised	146,20 € / Stk
106694	5/3-way, mid-position closed	144,45 € / Stk
106691	5/2-way, monostable	102,91 € / Stk
106692	5/2-way, monostable (uses only one pin, two signals assigned)	103,85 € / Stk

Created on: 18. Juni 2020 **User**: Gast

Page: 2 / 2