


Datasheet for: 102951


2/2-solenoid valve,NO,pilot opera., 230-240V,NBR,G1 1/4,0.2-10bar

2/2-way solenoid valve brass, NO, pilot operated, 230-240V, 50-60Hz, 16VA, Medium temp. -10°C to 90°C, NBR, G 1 1/4, PN 0.2-10bar . Economy series available in three different versions - Directly operated - Combined operation - Pilot-operated For all applications with compressed air, neutral gases or low-viscosity, neutral media.

Type number	MV 1385
Article number	102951
EAN/barcode	 4047322159609
Your price	237,18 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	54.0 mm
B	144.0 mm
DN	35.0
Electrical connection	For connector socket Pg 9/Pg 11 acc. to ISO 4400
Function	normally open (NO)
Housing	Brass
Internal parts	Stainless steel
Max. ambient temperature	80 °C
Max. medium temperature	90 °C
Max. operating pressure	10 bar
Min. ambient temperature	-10 °C
Min. medium temperature	-10 °C
Min. operating pressure	0.2 bar
Page No.	HK322
Protection IP	IP 65 (with connector socket fitted)
Sealant	NBR
Thread	G 1 1/4
Type	6
Valve seat	Brass

Variants

Article number	Thread	Max. operating pressure	DN	Type	Price
102951	G 1 1/4	10 bar	35.0	6	237,18 € / Stk
102947	G 3/8	16 bar	13.0	4	88,19 € / Stk
102948	G 1/2	16 bar	13.0	4	88,19 € / Stk
102949	G 3/4	16 bar	19.0	6	119,40 € / Stk
102950	G 1	16 bar	25.0	6	129,08 € / Stk
102952	G 1 1/2	10 bar	40.0	6	249,98 € / Stk
102953	G 2	10 bar	50.0	6	333,96 € / Stk

More Pictures

