


## Datasheet for: 108421


**Combined vacuum / pressure switch, Polycarbonate**

Combined vacuum / pressure switch, Polycarbonate, Measurement range -1-10 bar, Plug M8, 4-pole, G 1/8 ET, M5 IT, Temp. 0°C to 50°C . Universal electronic vacuum and pressure switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation directly at the point of use. Suitable for all special applications in the vacuum and compressed air sectors. Adjustable vacuum limit value and continuous vacuum monitoring.

Type number	VS 29
Article number	108421
EAN/barcode	 4047322203982
Your price	147,38 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Current consumption	30.0 mA
Electrical connection	Male connector M8, four pin
G 1	G 1/8 ET
G 2	M5 IT
G 3	M8x1 ET
Housing	Polycarbonate
Hysteresis	Adjustable: 3 to 25% of set value
Indication	LED
L	44.0 mm
L1	62.0 mm
Max. temperature range	50 °C
Measured medium connection	G 1/8 ET and M5 IT
Measuring range max. bar	10.0
Measuring range min. bar	-1.0
Medium	Non-aggressive gases; dry, oil-free air
Operating voltage	10.8 to 30 V DC
Output signal	Analogue: 1 to 5 V
Page No.	WEB

Switching capacity  
Type of construction

125 mA

PNP

### More Pictures

