


Datasheet for: 125341


Service unit 3-part »variobloc«, Metal container, Size 1, G 3/8

Service unit 3-part »variobloc«, Metal container incl. viewing tube and metal drip cap, Size 1, G 3/8, Input pressure max. 20 bar . Three-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator. Approved series in modern industrial design, with the following key benefits: - Simple handling - Convenient modular assembly thanks to innovative fasteners - Excellent flow values

Type number	VW 13 M
Article number	125341
EAN/barcode	 4047322170116
Your price	187,42 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	144.0 mm
B	201.0 mm
Bowl	Metal container with viewing tube
C	68.0 mm
Condensate drain	Manual
Diaphragms	NBR
Filter rating	40.0 μm
Flow rate	1800 l/min
Flow rate measurement	At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	80 °C
Max. control range	10.0 bar
Max. input pressure	20 bar
Max. medium temperature	50 °C
Min. control range	0.5 bar
Page No.	WEB

Pressure gauge display max.	10.0 bar
Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	variobloc
Sight dome	PA
Size	1
Spring bonnet	POM
Thread	G 3/8

Variants

Article number	Thread	Flow rate	Size	Price
125341	G 3/8	1800 l/min	1	187,42 € / Stk
125340	G 1/4	1500 l/min	1	187,42 € / Stk
125342	G 1/2	3400 l/min	2	263,26 € / Stk
125343	G 3/4	5000 l/min	2	263,26 € / Stk
125344	G 1	5000 l/min	2	296,58 € / Stk

More Pictures

