


Datasheet for: 108431



Vacuum switch, Polycarbonate, Plug M8, 4-pole, G 1/8 ET, M5 IT

Vacuum switch, Polycarbonate, Plug M8, 4-pole, G 1/8 ET, M5 IT, M8x1 ET, Temperature °C to 50 °C, 10.8 - 30 V DC . Universal electronic vacuum switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation directly on the suction pad. Switching point and hysteresis adjustable with a screw. Integrated LED for indication of the switching state.

Type number	VS 27
Article number	108431
EAN/barcode	 4047322201247
Your price	147,38 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Current consumption	30.0 mA
Electrical connection	Male connector M8, four pin
G 1	G 1/8 ET
G 2	M5 IT
G 3	M8x1 ET
Housing	Polycarbonate
Hysteresis	Adjustable: 3 % to 25 % of set value
L	44.0 mm
L1	62.0 mm
Max. temperature range	50 °C
Measured medium connection	G 1/8 ET and M5 IT
Measuring range max. bar	0.0
Measuring range min. bar	-1.0
Medium	Non-aggressive gases; dry, oil-free air
Operating voltage	10.8 to 30 V DC
Output signal	Analogue: 1 to 5 V
Page No.	WEB
Switching capacity	125 mA

Switching function

PNP

More Pictures

