


Datasheet for: 106603


5/2-way valve, Both sides pneumatic, bistable, G 1/2, DN 15

5/2-way valve, Both sides pneumatic, bistable, G 1/2, DN 15, Operating pre. 2.5 to 10 bar, Operating temp. -10 °C to 60 °C . This valve design, featuring the Tapered Tee Seal®, offers the ability to run without lubrication and supports almost any compressed air quality. The valves are largely resistant to dirt and can thus also be used under extreme conditions without any problems. Leakage is now a thing of the past and the spool no longer sticks, even after long idle periods.

Type number	517.633
Article number	106603
EAN/barcode	 4047322278676
Your price	240,42 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Connection	G 1/2
DN	15.0
Electrical connection	Coupler plug PG 9, form B
Flow rate 1	4600 NI/min
Flow rate measurement 1	Flow rate at 6 bar and Δp 1.0 bar
Function	5/2
Housing	Anodised aluminium, blue
Manual control	non-latching
Max. operating pressure	10 bar
Max. temperature range	60 °C
Min. operating pressure	2.5 bar
Min. pilot pressure	2.5 bar
Min. temperature range	-10 °C
Operation	Bistable
Page No.	HK473
Protection IP	IP 65 (DIN 46244)
Sealant	NBR
Spool	Stainless steel
Symbol	28

Variants

Article number	Connection	DN	Flow rate 1	Price
106603	G 1/2	15.0	4600 NI/min	240,42 € / Stk
106602	G 1/4	7.5	1500 NI/min	106,69 € / Stk

More Pictures

