


## Datasheet for: 101175



### Filter for high pressures up to 60 bar, 40 $\mu\text{m}$ , G 1/2

Filter for high pressures up to 60 bar, with manual bleeder valve, 40  $\mu\text{m}$ , G 1/2, Brass container, Operating temp. °C to 90 °C . Centrifugal separator with a sintered filter element.

Type number	680.32
Article number	101175
EAN/barcode	 4047322270328
Your price	187,45 € / Stk

### Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

### Productdata

A	65.0 mm
B	187.0 mm
Bowl	Brass
C	25.0 mm
Condensate drain	Manual drain valve
Filter rating	40.0 $\mu\text{m}$
Flow rate	2660 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 0.5$ bar
Housing	Aluminium
Max. input pressure	60 bar
Max. operating temperature	90 °C
Page No.	HK144
Sealant	NBR
Thread	G 1/2

## Variants

Article number	Thread	Flow rate	Price
101175	G 1/2	2660 l/min	187,45 € / Stk
101177	G 1	6000 l/min	228,17 € / Stk
101176	G 3/4	6000 l/min	233,44 € / Stk
101174	G 3/8	2660 l/min	184,98 € / Stk

## More Pictures

