

Datasheet for: 100579


**Service unit 2-part »multifix«, Metal container, Size 3, G 3/4**

Service unit 2-part »multifix«, Metal container, Viewing tube, Size 3, G 3/4, Input pressure max. 20 bar, Control range 0.5-10 bar . Two-piece service units consisting of a reversible diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number CL 34 M-SR

Article number 100579

EAN/barcode



4047322125437

Your price 190,45 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	134.8 mm
B	248.2 mm
Bowl	Metal container with viewing tube
C	99.0 mm
Condensate drain	Semi-automatic
D	149.2 mm
DN	20.0
Filter rating	5.0 $\mu$ m
Flow rate	3500 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast zinc
Max. ambient temperature	60 °C
Max. control range	10.0 bar
Max. input pressure	20 bar
Max. medium temperature	60 °C
Min. control range	0.5 bar
Page No.	HK091
Pressure gauge display max.	16.0 bar

Pressure gauge display min.	0.0 bar
Sealant	NBR
Series	multifix
Sight dome	Zinc-glass-NBR
Size	3
Spring bonnet	POM-brass
Thread	G 3/4

## Variants

Article number	Thread	Housing	Filter rating	Flow rate	Size	DN	Price
100579	G 3/4	Die-cast zinc	5.0 $\mu\text{m}$	3500 l/min	3	20.0	190,45 € / Stk
100576	G 1/4	Die-cast zinc	5.0 $\mu\text{m}$	1100 l/min	1	6.0	139,46 € / Stk
100577	G 3/8	Die-cast zinc	5.0 $\mu\text{m}$	1100 l/min	1	10.0	142,91 € / Stk
100578	G 1/2	Die-cast zinc	5.0 $\mu\text{m}$	3500 l/min	3	15.0	188,60 € / Stk
100580	G 1	Aluminium	40.0 $\mu\text{m}$	10500 l/min	5	25.0	507,88 € / Stk
133125	G 3/4	Die-cast aluminium	5.0 $\mu\text{m}$	9500 l/min	4	20.0	419,74 € / Stk
133126	G 1	Die-cast aluminium	5.0 $\mu\text{m}$	9500 l/min	4	25.0	419,74 € / Stk

## More Pictures

