

Datasheet for: 137348


Stainless steel casting filter, 1.4401, 25 µm, Size 1, G 3/8

Stainless steel casting filter, 1.4401, 25 µm, Size 1, G 3/8, Input pressure max. 30 bar, Medium temperature max. 80 °C . Stainless steel filters for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc.

| | |
|-------------|-----------|
| Type number | 580FC1-38 |
|-------------|-----------|

| | |
|----------------|--------|
| Article number | 137348 |
|----------------|--------|

| | |
|-------------|--|
| EAN/barcode |  4047322513319 |
|-------------|--|

| | |
|------------|----------------|
| Your price | 242,08 € / Stk |
|------------|----------------|

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|---|
| A | 64.0 mm |
| B | 127.0 mm |
| C | 113.0 mm |
| Condensate drain | Locking screw |
| Filter rating | 25.0 µm |
| Flow rate | 2920 l/min |
| Flow rate measurement | At P ₁ = 6 bar and pressure drop $\Delta_p \leq 1$ bar |
| Housing | Stainless steel casting 1.4401 (AISI 316) |
| Max. ambient temperature | 60 °C |
| Max. input pressure | 30 bar |
| Max. medium temperature | 80 °C |
| Page No. | HK154 |
| Sealant | NBR |
| Size | 1 |
| Thread | G 3/8 |

Variants

| Article number | Thread | Flow rate | Size | Price |
|----------------|---------|------------|------|----------------|
| 137348 | G 3/8 | 2920 l/min | 1 | 242,08 € / Stk |
| 137347 | G 1/4 | 2010 l/min | 1 | 242,08 € / Stk |
| 137349 | G 1/2 | 5355 l/min | 3 | 281,74 € / Stk |
| 137350 | G 3/4 | 6855 l/min | 3 | 281,74 € / Stk |
| 137351 | G 1 | 9910 l/min | 4 | 904,13 € / Stk |
| 137352 | G 1 1/2 | 9910 l/min | 4 | 904,13 € / Stk |

More Pictures

