

Datasheet for: 101570



Microfilter without differential pressure gauge, 0.01 μm , G 1/2

Microfilter without differential pressure gauge, 0.01 μm , G 1/2, Input pressure 4 - 16 bar, Medium / ambient temp. 5 °C to 60 °C . Ideal for filtering out aerosols and solid impurities larger than 0.01 μm . Micro-filters should always be used in conjunction with a pre-filter.

Type number	430.5106
-------------	----------

Article number	101570
----------------	--------

EAN/barcode	
-------------	--



4047322086912

Your price	243,06 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	83.0 mm
B2	335.0 mm
C	57.0 mm
D	353.0 mm
Efficiency	99.9999 %
Filter element	Borosilicate (with glass-fibre material and foam plastic)
Filter rating	0.01 μm
Flow rate	1300 l/min
Flow rate measurement	At $P_1 = 6$ bar and pressure drop $\Delta_p = 1.5\%$
Housing	Aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. ambient temperature	5 °C
Min. input pressure	4.0 bar
Min. medium temperature	5 °C
Page No.	HK138
Thread	G 1/2
filter bowl	Aluminium

Variants

Article number	Thread	Flow rate	Price
101570	G 1/2	1300 l/min	243,06 € / Stk
101568	G 1/4	1300 l/min	243,63 € / Stk
101569	G 3/8	1300 l/min	241,21 € / Stk
101571	G 3/4	2000 l/min	280,54 € / Stk
101572	G 1	4080 l/min	407,67 € / Stk
101573	G 1 1/4	4580 l/min	466,62 € / Stk
101574	G 1 1/2	6500 l/min	514,03 € / Stk
101575	G 2	9000 l/min	643,69 € / Stk

More Pictures

