

## Datasheet for: 101586



**Active charcoal filter without differential pressure gauge, G 1/2**

Active charcoal filter without differential pressure gauge, 0.005 mg/m<sup>3</sup>, G 1/2, Input pressure 4 - 16 bar, Temp. 5 °C to 60 °C . For adsorbing vaporous media. A micro-filter must be connected upstream if dried air is not available.

Type number	431.5106
-------------	----------

Article number	101586
----------------	--------

EAN/barcode	
-------------	--



4047322087162

Your price	191,26 € / Stk
------------	----------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	83.0 mm
B2	245.0 mm
C	57.0 mm
D	263.0 mm
Filter element	Activated carbon
Flow rate	500 l/min
Flow rate measurement	At P <sub>1</sub> = 6 bar and pressure drop Δ <sub>p</sub> = 0.5%
Housing	Aluminium
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Min. ambient temperature	5 °C
Min. input pressure	4.0 bar
Min. medium temperature	5 °C
Page No.	HK139
Residual oil content	0.005 mg/m <sup>3</sup>
Thread	G 1/2
filter bowl	Aluminium

## Variants

Article number	Thread	Flow rate	Price
101586	G 1/2	500 l/min	191,26 € / Stk
101584	G 1/4	500 l/min	192,30 € / Stk
101585	G 3/8	500 l/min	191,73 € / Stk
101587	G 3/4	1000 l/min	229,91 € / Stk
101588	G 1	1500 l/min	355,76 € / Stk
101589	G 1 1/4	2650 l/min	410,44 € / Stk
101590	G 1 1/2	4150 l/min	466,15 € / Stk
101591	G 2	6650 l/min	598,81 € / Stk

## More Pictures

