

Datasheet for: 108389

Basic ejector »SBP-C«, Bleeder valve, Silencer, Nozzle size 1 mm

Basic ejector »SBP-C«, Bleeder valve, Silencer, Nozzle size 1 mm, Compressed air / vacuum connection 6/8 mm, NO . Purely pneumatic vacuum generator that operates on the Venturi principle. Compressed air enters the ejector at A and flows through the nozzle B. This results in a vacuum immediately behind the nozzle outlet, and air is drawn in through the vacuum inlet D. This air and the driving air leave the ejector via the silencer C. Properties:

- Vacuum generator with a single nozzle, available in six power ratings, with a high maximum vacuum value (85%)

- Connection of compressed air and vacuum with push-in coupling

- Basic housing with connection facility for a vacuum switch

- Maximum suction capacity with minimum compressed air consumption

- Minimum size, low weight

- Various power ratings for optimised air consumption

Applications:


- For universal use in handling systems with very high dynamic movements

- Handling all kinds of air-tight components

- For use in separation systems where space is restricted

- Construction of ejector blocks for centralised or decentralised individual control of suction pads



Type number	SBPC 10
Article number	108389
EAN/barcode	 4047322198844
Your price	191,35 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Body Plastic (impact-resistant)

Compressed air inlet	6 mm
Connection	Push-in coupling
Height	50.0 mm
Length	142.0 mm
Nozzle size	1.0 mm
Nozzle system	Brass
Page No.	WEB
Silencer	Plastic
Suction valve idle position	NO
Vacuum inlet	8 mm
Width	15.0 mm

Variants

Article number	Nozzle size	Compressed air inlet	Vacuum inlet	Price
108389	1.0 mm	6 mm	8 mm	191,35 € / Stk
108390	1.5 mm	6 mm	8 mm	200,15 € / Stk
108391	2.0 mm	8 mm	10 mm	229,61 € / Stk
108392	2.5 mm	8 mm	10 mm	242,26 € / Stk

More Pictures

