

## Datasheet for: 103598



**Stainless steel ball valve, Pneumat. actuation drive, Rp 3/4**

2-way stainless steel ball valve, Pneumat. actuation drive, double-acting, Operating temp. -20°C to 70°C, Rp 3/4, PN max. 63 bar . 2-way cock, 3-piece, full bore. Pneumatic actuators, double- or single acting version and integrated end-position feedback. Standardised interfaces:  
 Actuator/valve interface: Four or eight female threads in the actuator housing acc. to EN ISO 5211. Actuator/control valve interface: Acc. to NAMUR or VDI/VDE 3845.  
 Actuator/signalling device interface: Acc. to VDI/VDE 3845 (NAMUR).

|             |           |
|-------------|-----------|
| Type number | 350.511/1 |
|-------------|-----------|

|                |        |
|----------------|--------|
| Article number | 103598 |
|----------------|--------|

|             |  |
|-------------|--|
| EAN/barcode |  |
|-------------|--|



4047322076494

|            |                |
|------------|----------------|
| Your price | 244,75 € / Stk |
|------------|----------------|

**Minimum order quantity**

|                        |       |
|------------------------|-------|
| Price Unit             | 1     |
| Quantity Unit          | Stk   |
| Packaging Unit         | 1     |
| Content                | 1 Stk |
| Minimum order quantity | 1     |

**Productdata**

|                            |   |
|----------------------------|---|
| A                          | 116.0 mm                                      |
| Angle of rotation          | 90 °  |
| B                          | 139.0 mm                                      |
| D                          | 27.0 mm                                       |
| DN                         | 20.0  |
| L                          | 80.0 mm                                       |
| Material actuator          | Anodised aluminium                            |
| Material ball valve        | Stainless steel 1.4401, with ISO flange plate |
| Max. operating pressure    | 63 bar  |
| Max. operating temperature | 70 °C   |
| Max. pilot pressure        | 5.5 bar                                       |
| Min. operating temperature | -20 °C  |
| Page No.                   | HK302   |
| Sealant actuator           | NBR   |
| Sealant ball valve         | PTFE  |
| Thread                     | Rp 3/4  |

Valve adapter  
 Version  
 a/f

 Acc. to NAMUR  
 double-acting  
 35 mm

## Variants

| Article number | Thread   | DN   | a/f    | Price            |
|----------------|----------|------|--------|------------------|
| 103598         | Rp 3/4   | 20.0 | 35 mm  | 244,75 € / Stk   |
| 103595         | Rp 1/2   | 15.0 | 29 mm  | 268,03 € / Stk   |
| 103596         | Rp 1/2   | 15.0 | 29 mm  | 229,12 € / Stk   |
| 103597         | Rp 3/4   | 20.0 | 35 mm  | 284,58 € / Stk   |
| 103599         | Rp 1     | 25.0 | 41 mm  | 347,24 € / Stk   |
| 103600         | Rp 1 1/4 | 32.0 | 50 mm  | 415,05 € / Stk   |
| 103601         | Rp 1 1/2 | 40.0 | 58 mm  | 474,81 € / Stk   |
| 103602         | Rp 2     | 50.0 | 74 mm  | 542,73 € / Stk   |
| 103603         | Rp 2 1/2 | 65.0 | 89 mm  | 943,44 € / Stk   |
| 103604         | Rp 3     | 80.0 | 104 mm | 1.209,50 € / Stk |

## More Pictures

