


Datasheet for: 100969


Filter »Standard«, PC container, Protective cage, Size 4, G 1 1/4

Filter »Standard«, PC container, Protective cage, 40 μm , Size 4, G 1 1/4, Input pressure max. 16 bar, Med./ambient temp. max. 60°C . Centrifugal separators with a sintered filter element.

Type number	650 F/S
Article number	100969
EAN/barcode	 4047322110396
Your price	247,65 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	125.0 mm
Bowl	Polycarbonate container with protective cage
C	36.5 mm
Condensate drain	Semi-automatic
D	243.4 mm
DN	40.0
Filter rating	40.0 μm
Flow rate	12500 l/min
Flow rate measurement	At $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
H	105.0 mm
Housing	Die-cast zinc, painted silver
Max. ambient temperature	60 °C
Max. input pressure	16 bar
Max. medium temperature	60 °C
Page No.	HK125
Series	Standard
Size	4
Thread	G 1 1/4

Variants

Article number	Thread	Filter rating	Flow rate	Size	DN	Price
100969	G 1 1/4	40.0 μm	12500 l/min	4	40.0	247,65 € / Stk
100963	G 1/4	5.0 μm	800 l/min	1	6.0	37,50 € / Stk
100964	G 3/8	5.0 μm	800 l/min	1	6.0	37,50 € / Stk
100965	G 3/8	40.0 μm	3100 l/min	2	10.0	62,55 € / Stk
100966	G 1/2	5.0 μm	4000 l/min	3	15.0	62,55 € / Stk
100967	G 3/4	5.0 μm	4000 l/min	3	20.0	119,63 € / Stk
100968	G 1	5.0 μm	4000 l/min	3	25.0	119,63 € / Stk
100970	G 1 1/2	40.0 μm	12500 l/min	4	45.0	209,22 € / Stk
100971	G 2	60.0 μm	30000 l/min	5	55.0	579,52 € / Stk

More Pictures

