


## Datasheet for: 108432


**Pressure switch, Polycarbonate, Plug M8, 4-pole, G 1/8 ET, M5 IT**

Pressure switch, Polycarbonate, Plug M8, 4-pole, G 1/8 ET, M5 IT, M8x1 ET, Temperature °C to 50 °C, 10.8 - 30 V DC . Universal electronic pressure switch for safety monitoring, optimisation of cycle times and regulation circuits. Its small size and low weight permit installation in handling systems directly at the point of use.

Type number	VS 56
Article number	108432
EAN/barcode	 4047322203999
Your price	250,68 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Current consumption	55.0 mA
Electrical connection	Male connector M8, four pin
G 1	G 1/8 ET
G 2	M5 IT
G 3	M8x1 ET
Housing	Polycarbonate
Hysteresis	Adjustable: to 100 % of set value or comparator mode
Indication	2 x LED
L	58.5 mm
L1	75.5 mm
Max. temperature range	50 °C
Measured medium connection	G 1/8 ET and M5 IT
Measured value display	3-digit 7-segment LED
Measuring range max. bar	10.0
Measuring range min. bar	0.0
Medium	Non-aggressive gases; dry, oil-free air
Operating voltage	10.8 to 30 V DC
Output signal	2 x digital
Page No.	WEB

Switching capacity  
Type of construction

180 mA

PNP

### More Pictures

