


## Datasheet for: 158751


**Brass ball valve, Pneum. actuation drive, single-acting, Rp 1 1/2**

Brass ball valve, Pneumat. actuation drive, NAMUR, single-acting, Operating temp. -20°C to 150°C, Rp 1 1/2, DN 40, PN max. 16 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Type number	351.314-1
Article number	158751
EAN/barcode	 4047322635394
Your price	254,16 € / Stk

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

A	233.2 mm
Angle of rotation	90 °
B	136.8 mm
DN	40.0
L	114.0 mm
Material actuator	Anodised aluminium
Material ball valve	Nickel-plated brass, with flange plate ISO 5211
Max. Operating pressure ball valve	150 °C
Max. operating pressure ball valve	16 bar
Max. operating temperature actuator	80 °C
Max. pilot pressure actuator	8.4 bar
Min. Operating pressure ball valve	-20 °C
Min. operating temperature actuator	-20 °C
Page No.	HK301
Recommended pilot pressure	5.6 bar

Sealant actuator	NBR
Sealant ball valve	PTFE / FKM
Thread	Rp 1 1/2
Valve adapter	Integrated to NAMUR
Version	single-acting - spring to close

## Variants

Article number	Thread	DN	Price
158751	Rp 1 1/2	40.0	254,16 € / Stk
158747	Rp 1/2	15.0	200,88 € / Stk
158752	Rp 2	50.0	344,88 € / Stk
158746	Rp 3/8	10.0	200,16 € / Stk
158748	Rp 3/4	20.0	207,36 € / Stk
158750	Rp 1 1/4	32.0	233,28 € / Stk
158749	Rp 1	25.0	216,00 € / Stk

## More Pictures

