

Datasheet for: 158757


Stainless steel ball valve, Pneumatic actuation drive, Rp 1 1/4

Stainless steel ball valve, Pneumatic actuation drive, double-acting, Operating temp. -20 °C to 150 °C, Rp 1 1/4, PN max. 64 bar . Ball valves with pneumatic actuator. Pneumatic, double-piston, part-turn actuator, double-rocker principle.

Type number	351.513-1
-------------	-----------

Article number	158757
----------------	--------

EAN/barcode



4047322635189

Your price	353,72 € / Stk
------------	----------------

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	188.5 mm
Angle of rotation	90 °
B	188.5 mm
DN	32.0
L	95.0 mm
Material actuator	Anodised aluminium
Material ball valve	Stainless steel 1.4401/1.4301/1.4310/1.4408, with ISO flange
Max. Operating pressure ball valve	150 °C
Max. operating temperature actuator	80 °C
Max. pilot pressure actuator	8.4 bar
Min. Operating pressure ball valve	-20 °C
Min. operating temperature actuator	-20 °C
PN	64 bar
Page No.	HK304
Recommended pilot pressure	5.6 bar
Sealant actuator	NBR

Sealant ball valve
Thread
Valve adapter
Version

PTFE / FKM
Rp 1 1/4
Integrated to NAMUR
double-acting

Variants

Article number	Thread	DN	PN	Price
158757	Rp 1 1/4	32.0	64 bar	353,72 € / Stk
158754	Rp 1/2	15.0	100 bar	235,50 € / Stk
158755	Rp 3/4	20.0	100 bar	272,84 € / Stk
158758	Rp 1 1/2	40.0	64 bar	407,52 € / Stk
158756	Rp 1	25.0	100 bar	298,68 € / Stk
158753	Rp 3/8	10.0	100 bar	231,04 € / Stk
158759	Rp 2	50.0	40 bar	543,12 € / Stk

More Pictures

