


Datasheet for: 116382



Service unit 2-part »G«, Metal container, 5 μ m, Size 600, G 3/4

Service unit 2-part »G«, Metal container, Viewing tube, 5 μ m, Size 600, G 3/4, Input pressure max. 10 bar, Control range 1.5-9 bar. Two-piece service units consisting of a diaphragm pressure regulator, independent of inlet pressure, with self-relieving design, combined with a centrifugal separator and a proportional lubricator.

Type number	GCL 34
Article number	116382
EAN/barcode	 4047322307628
Your price	254,19 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

A	190.0 mm
B	363.0 mm
Bowl	Metal container with viewing tube
C	144.0 mm
Condensate drain	Semi-automatic
D	219.0 mm
Filter rating	5.0 μ m
Flow rate	4200 l/min
Flow rate measurement	At $P_1 = 8$ bar, $P_2 = 6$ bar and pressure drop $\Delta_p = 1$ bar
Housing	Die-cast aluminium
Max. ambient temperature	70 °C
Max. control range	9.0 bar
Max. input pressure	10 bar
Max. medium temperature	70 °C
Min. control range	1.5 bar
Page No.	WEB
Page No. AS	AS032
Sealant	NBR

Series G
 Sight dome Brass/POM
 Size 600
 Spring bonnet POM
 Thread G 3/4

Variants

<i>Article number</i>	<i>Thread</i>	<i>Condensate drain</i>	<i>Price</i>
116382	G 3/4	Semi-automatic	254,19 € / Stk
116385	G 1	Fully-automatic	276,43 € / Stk
116384	G 1	Semi-automatic	254,19 € / Stk
116383	G 3/4	Fully-automatic	276,43 € / Stk

More Pictures

