

Datasheet for: 102747


Pressure transducer, - 16 bar, G 1/4, CrNi steel 1.4404

Pressure transducer for general industrial applications, Non-linearity 0.5%, Measurement range 0-16 bar, G 1/4, CrNi steel 1.4404 . Standard type for universal applications. Suitable for electronic pressure measurements in the low and high-pressure ranges.

| | |
|----------------|--|
| Type number | 895.21 |
| Article number | 102747 |
| EAN/barcode |  4047322277099 |
| Your price | 192,31 € / Stk |

Minimum order quantity

| | |
|------------------------|-------|
| Price Unit | 1 |
| Quantity Unit | Stk |
| Packaging Unit | 1 |
| Content | 1 Stk |
| Minimum order quantity | 1 |

Productdata

| | |
|--------------------------|--|
| Electrical connection | With right-angle connector acc. to DIN EN 175301-803 A |
| Housing | CrNi steel 1.4404 |
| Max. ambient temperature | 80 °C |
| Max. medium temperature | 80 °C |
| Measuring range max. bar | 16.0 |
| Measuring range min. bar | 0.0 |
| Nonlinearity | 0.5% of span |
| Operating voltage | 8 to 30 V |
| Output signal | 4 - 20 mA, 2-wire |
| Page No. | HK235 |
| Protection IP | IP 65 acc. to EN 60529 |
| Thread | G 1/4 |
| Type | A-10 |
| Wetted parts | CrNi steel 1.4404 |

Variants

| <i>Article number</i> | <i>Measuring range max. bar</i> | <i>Price</i> |
|-----------------------|---------------------------------|----------------|
| 102747 | 16.0 | 192,31 € / Stk |
| 102745 | 6.0 | 192,31 € / Stk |
| 102746 | 10.0 | 192,31 € / Stk |
| 102744 | 4.0 | 192,31 € / Stk |
| 102750 | 60.0 | 192,31 € / Stk |
| 102753 | 250.0 | 192,31 € / Stk |
| 102754 | 400.0 | 192,31 € / Stk |
| 102752 | 160.0 | 192,31 € / Stk |
| 102755 | 600.0 | 192,31 € / Stk |
| 102743 | 2.5 | 192,31 € / Stk |
| 102751 | 100.0 | 192,31 € / Stk |
| 102748 | 25.0 | 192,31 € / Stk |
| 102741 | 1.0 | 192,31 € / Stk |
| 102749 | 40.0 | 192,31 € / Stk |
| 102742 | 1.6 | 192,31 € / Stk |