

Datasheet for: 105647



Corner safety valve, liquids, G 2, Trigger pressure 7 bar

Corner safety valve, for liquids, Red brass, Operating temp. -10 °C to 110 °C, G 2, AF 70, Trigger pressure 7 bar . For non-toxic, non-flammable liquids. No evaporation allowed when blowing off. With diaphragm to protect the spring and with lifting device. Type-tested, TÜV-SV. 749. F

Type number 221.08-7,0

Article number 105647

EAN/barcode



4047322039796

Your price 353,89 € / Stk

Minimum order quantity

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

Productdata

Adjustment range max.	16.0 bar
Adjustment range min.	1.0 bar
Diaphragms	NBR
H	200.0 mm
Housing	Bronze
Inlet and outlet	Each with female thread acc. to DIN EN ISO 228-1
Internal parts	Brass
L1	56.0 mm
L2	48.0 mm
Max. operating temperature	110 °C
Min. operating temperature	-10 °C
Min. set pressure	7.0 bar
Page No.	HK367
Page No. SF	SF060
Spring	C steel
Spring bonnet	Brass
Thread	G 2
a/f	70 mm

Variants

Article number	Min. set pressure	Price
105647	7.0 bar	353,89 € / Stk
105639	2.0 bar	353,89 € / Stk
105640	2.5 bar	353,89 € / Stk
105641	3.0 bar	353,89 € / Stk
105643	4.0 bar	353,89 € / Stk
105646	6.0 bar	353,89 € / Stk
105637	1.0 bar	353,89 € / Stk
105648	10.0 bar	353,89 € / Stk
105638	1.7 bar	353,89 € / Stk
105649	13.0 bar	353,89 € / Stk
105644	4.5 bar	353,89 € / Stk
105645	5.5 bar	353,89 € / Stk
105642	3.5 bar	353,89 € / Stk
151278	1.6 bar	353,89 € / Stk
137686	1.5 bar	353,89 € / Stk
179347	7.5 bar	353,89 € / Stk

More Pictures

