

## Datasheet for: 125307


**Corner safety valve, G 2, Trigger pressure 3.5 bar**

Corner safety valve, for saturated steam, Red brass,  
 Operating temp. -10 to 185 °C, G 2, AF 70, Trigger pressure  
 3.5 bar . Type-tested, TÜV – SV. 749 D/G

Type number	222.08-3,5
-------------	------------

Article number	125307
----------------	--------

EAN/barcode	 4047322365826
-------------	----------------------------------------------------------------------------------------------------

Your price	353,89 € / Stk
------------	----------------

**Minimum order quantity**

Price Unit	1
Quantity Unit	Stk
Packaging Unit	1
Content	1 Stk
Minimum order quantity	1

**Productdata**

Adjustment range max.	20.0 bar
Adjustment range min.	0.2 bar
Diaphragms	PTFE
H	200.0 mm
Housing	Bronze
Inlet and outlet	Open
Internal parts	Brass
L1	56.0 mm
L2	48.0 mm
Max. operating temperature	185 °C
Min. operating temperature	-10 °C
Min. set pressure	3.5 bar
Page No.	HK366
Page No. SF	SF059
Spring	C steel
Spring bonnet	Brass
Thread	G 2
a/f	70 mm

## Variants

<i>Article number</i>	<i>Min. set pressure</i>	<i>Max. operating temperature</i>	<i>Diaphragms</i>	<i>Price</i>
125307	3.5 bar	185 °C	PTFE	353,89 € / Stk
105517	0.2 bar	135 °C	EPDM	353,89 € / Stk
105521	1.5 bar	135 °C	EPDM	353,89 € / Stk
105519	0.5 bar	135 °C	EPDM	353,89 € / Stk
105518	0.4 bar	135 °C	EPDM	353,89 € / Stk
105522	1.6 bar	135 °C	EPDM	353,89 € / Stk
105520	1.2 bar	135 °C	EPDM	353,89 € / Stk
125306	3.0 bar	185 °C	PTFE	353,89 € / Stk
117645	2.0 bar	135 °C	EPDM	353,89 € / Stk
117644	0.8 bar	135 °C	EPDM	353,89 € / Stk

## More Pictures

